

# **Ceiling Blanket Insulation**

### Mammoth ceiling blankets are designed to be installed in new or existing roof cavities.

An effective and easy form of thermal insulation, Mammoth® Modern Insulation ceiling blankets have a range of R-values of up to R4.0, or R8.0 when double layered. Mammoth blankets are long lasting, won't sag or settle over time, are non-irritant and highly effective. Mammoth products contain recycled polyester fibres. Mammoth ceiling blanket insulation uses up to 7,400 recycled plastic bottles per 100sqm\*.

For new ceilings without a roof space there is the option of our <u>Mammoth Skillion Ceiling Sections</u> and for skillion and truss roofs we have <u>Mammoth</u> <u>Ceiling Battens</u>.

#### Can be double layered to meet the new Building Code.

Mammoth ceiling blankets are manufactured in roll form so that they can be installed as both a single or double layer system. For any system - single or double layered - the joist depth must be greater than the insulation thickness.

Mammoth ceiling blankets are designed in widths to fit snugly between joists or trusses in a single layer option or alternatively with a second layer run perpendicular to the first, covering the top of the joists or truss bottom chord reducing thermal bridging in these areas.

PRODUCT RANGE					PACK SIZES			
	Eco <sup>°</sup> Choice Aotearoa	BRANZ Appraised	Density (kg/m3)	R-Value	Nominal thickness (mm)	Dimensions (mm)	Pieces per pack	Area per pack (m2)
Ceiling Blanket	$\checkmark$	$\checkmark$	7.83	R 1.8	115	870 x 11495	2	20
	$\checkmark$	$\checkmark$	7.57	R 2.9	185	870 x 8620	2	15
	$\checkmark$	$\checkmark$	8.00	R 3.2	200	870 x 8620	2	15
	$\checkmark$	$\checkmark$	8.00	R 3.3	210	870 x 8620	2	15
	$\checkmark$	$\checkmark$	8.00	R 3.6	225	870 x 7470	2	13
	$\checkmark$	$\checkmark$	8.33	R 4.0	240	870 x 5750	2	10
Double Layer - R 2.9 x 2	$\checkmark$		7.57	R 5.8	370	870 x 8620	2	15*
Double Layer - R 3.2 x 2	$\checkmark$		8.00	R 6.4	400	870 x 8620	2	15*
Double Layer - R 3.3 x 2	$\checkmark$		8.00	R 6.6	420	870 x 8620	2	15*
Double Layer - R 3.6 x 2	$\checkmark$		8.00	R 7.2	450	870 x 7470	2	13*
Double Layer - R 4.0 x 2	$\checkmark$		8.33	R 8.0	480	870 x 5750	2	10*

For any system - single or double layered - the joist depth must be greater than the insulation thickness.

\* For Double Layering - Double the quantity of product is required. For instance, a 100m2 area requires 200m2 of product to achieve a double layer.

## **KEY FEATURES**

- Soft, roll-form 100% polyester insulation blanket for ceilings. Can be double layered for higher R-value.
- Mammoth ceiling blanket insulation uses up to 7,400 recycled plastic bottles per 100sqm<sup>\*</sup>. \* Calculations are based on 500ml PET Bottles (16.2g).
- Unaffected by moisture, Mammoth will continue to perform once dried out. Mammoth is moisture, mould and mildew resistant.
- Lightweight and easy to handle can easily be torn to length or cut with shears. Available in varying widths and lengths to suit most applications.
- Heat bonded no glues or binders that can break down so it won't sag or settle over time.
- Red List Free no formaldehyde or pesticides added.
- Safe, non-itch, odourless and non-toxic no precautions are required for handling the product.
- All Mammoth ceiling blankets are BRANZ 797 Appraised.
- All Mammoth ceiling blankets have Environmental Choice certification.
- Mammoth products are made in a zero waste production process and are fully recyclable.
- Mammoth ceiling insulation products have an ODP of zero.
- Long lasting, Mammoth insulation is performance warranted for 50 years (T&Cs apply).
- Manufactured by InZone Industries Ltd, NZ's first and only Toitū net carbonzero certified insulation manufacturing organisation.

# **TECHNICAL DETAILS**

Technical Attributes	Standard	Test Result		
New Zealand Building Code				
✓ Durability	Clause B2.3.1 a) 15 years Clause B2.3.1 b) 50 years	Ref: BRANZ Appraisal No 797 <sup>1</sup>		
<ul> <li>Internal Moisture</li> </ul>	Clause E3.3.1	Ref: BRANZ Appraisal No 797 <sup>1</sup>		
<ul> <li>Hazardous Building Materials</li> </ul>	Clause F2.3.1	Ref: BRANZ Appraisal No 797 <sup>1</sup>		
<ul> <li>Energy Efficiency</li> </ul>	Clause H1.3.1(a) Clause H1.3.2 E	Ref: BRANZ Appraisal No 797 <sup>1</sup>		
Product Safety				
🗸 Non Toxic	OSH Health and Safety Guidelines <sup>2</sup>	Polyester products are 'non-toxic'		
🗸 Non Irritant	OSH Health and Safety Guidelines <sup>2</sup>	Polyester products are 'non-irritant'		
<ul> <li>Respiratory Safe</li> </ul>	n/a	Polyester fibres are non-respirable		
✓ Fire Test	AS/NZS60695.2.11	Passed - Glow wire flammability test		
	AS/NZS60695.11.5	Passed - Test flames (Needle-flame test)		
	ISO9705	Group1S		
		Can safely cover IC-rated downlights. If luminare rating is unknown, minimum clearance of 100mm to any insulation is required.		
✓ VOC Emission Safe <sup>3</sup>	Total VOC $\leq$ 0.5mg/m <sup>3</sup>	< 0.005mg/m3 - level below detection <sup>4</sup>		
	Formaldehyde $\leq$ 0.06mg/m <sup>3</sup>	< 0.009mg/m3 - level below detection		
✓ Glue Free		Free from all glues		
Other				
✓ Non Corrosive	AS/NZS4859.1	Materials composed entirely of polyester are regarded as non-corrosive and are exempt from testing. Alkalinity of pH 7.8		
🗸 Vermin Resistant		Not a food source for vermin (and not treated)		

1 Meet or contribute to these provisions when designed, used, installed and maintained in accordance with BRANZ Appraisal 797.

2 Occupational Safety and Health Service. Health and Safety Guidelines for the Selection and Safe Handling of Synthetic Mineral Fibres, Dept of Labour, 1994.

*3 Mammoth has been tested under ASTM D5116. Based on test results for a product with similar nominal weight.* 

4 All individual VOCs were less than their threshold limit values. Carcinogens and reproductive toxins were not identified as part of the VOCs.

# **INSTALLATION & WARRANTY**

#### Installation

Mammoth Ceiling Insulation must be installed according to the manufacturer's guidelines and in accordance with NZS 4246 (Energy Efficiency - Installing Insulation in Residential Buildings). Installation Instructions for Mammoth Ceiling Insulation can be found <u>here</u>. Contact us on 0800 MAMMOTH for more details.

### 50 Year Warranty

Mammoth Insulation has a 50 year warranty. Our product warranty covers that - so long as the insulation is installed correctly and remains adequately protected Mammoth insulation will perform for 50 years. The warranty applies only to 100% polyester insulation products manufactured by InZone Industries Ltd. Read the <u>full warranty</u> for terms and conditions.

#### **BRANZ** Appraised

Mammoth Ceiling Insulation Blanket has been tested by, and is covered by BRANZ Appraisal 797.



Correct as at 24 April 2024



### **0800 MAMMOTH**

### www.mammoth.co.nz

Manufactured in New Zealand's North Island and South Island PO Box 204 289, Highbrook, Auckland 2161 Ph: 0800 626 668 | E: info@mammoth.co.nz \* Registered trade mark of InZone Industries Ltd