

EBSA Automated Louvres MP2 Louvre System PTS

Product Technical Statement: 114183



Double / Triple glazed large format system providing ultimate sustainability & efficiency.

[View miproducts listing](#)



Level of assurance needed to demonstrate NZ Building Code Compliance

Supporting documentation should include self-assessment and technical information by manufacturer



EBSA Automated Louvres confirms that this minimum level of assurance has been met or exceeded by the following:

Azuma Design Pty Ltd

[Wind and Water Penetration Testing - AZT0152.21](#)



The following information has been provided by EBSA Automated Louvres demonstrating how this product complies with the [Building Product Information Requirements](#).

Technical Statement

Product Class

CLASS 2

Product Description

The MP2 louvre system is specifically engineered to assist building designers to meet the requirements of H1 compliance in relation to the new stringent sections in the New Zealand regulations.

- Framed or frameless
- Double / triple glazed
- End pivot operation
- 144mm x 50mm thermally broken frame
- Louvre widths Up to 1500 mm
- Blade Height Up to 500mm
- Water Penetration up to 800Pa
- Air Infiltration +0.22 l/sm² (-0.22l/sm²)
- The use of IGU's and thermally broken frames is essential to achieve low R - values
- Ultimate up to 8000Pa
- Security (via integrated locking mechanism)
- Safety locking of each blade
- Integrated 24VDC drives

Scope of use

The MP2 louvre system is certified to NZS4211 having been tested to AS/NZS4420.1 .

With the correct glass selection and specification on thicknesses the MP2 louvre is capable of meeting energy provision requirements.

ACTUATORS

- Drive 24v D/C 600N Force
- 0.8Amp full load
- IP50
- 10000 double strokes in each direction
- Fire Stability 30min @ 300degrees
- Closing Edge Protection
- 5 Year Warranty D+H Actuator LD Series

MP2 LOUVRE

- Louvre profile 144mm x 50mm thermally broken
- Blade holders / fully framed or frameless & thermally broken
- Dimensions / frame width (min 650mm up to 1500mm)
- Dimensions / frame height (min 450mm to any height)
- IGU options / double glazed (32mm) stepped / triple glazed (42mm) stepped
- Operating details / 24v d/c mechanical operation / available in manual operation
- The MP2 is a louvre system that offers efficient, sustainability and compliant smoke relief to buildings.

New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- **Clause B2 Durability:** Performance B2.3.1, B2.3.1(c)



masterspec partner

Company Contact Details



Brand: EBSA Automated Louvres

Company: EBSA NZ Limited

Physical Address: Charann Place
Avondale
Auckland

Postal Address: PO Box 27261
Mount Roskill
Auckland

Telephone: 64 09 8840025

Email: sales@ebsa.co.nz

Website: <https://www.ebsa.co.nz/>

EBSA Automated Louvres MP2 Louvre System PTS

Product Technical Statement: 114183



1237 WARRANTIES for additional requirements

WARRANTY - INSTALLER/APPLICATOR

- Provide an installer/applicator warranty
- 5 years for fabrication and workmanship
- **Clause D2 Mechanical installations for access:** Performance D2.3.3(c), D2.3.3(d)

NATA Accredited Laboratory (Certificate Number 15147)

- AS/NZS 4420.1: 2016
- COMPLETE AIR SEAL

To NZBC E2/AS1, 9.1.6 air seals.

- Form an air-tight seal by means of proprietary sealants.

AIR INFILTRATION

For NZS 4211, table 3 air infiltration.

- Non-air conditioned zones (passive ventilation) and conditioned zones.

INFORMATION REQUIRED FOR CODE COMPLIANCE

- Installer's approval certificate from the manufacturer / importer / distributor
- Manufacturer's / supplier's warranty
- Installer's / applicator's warranty
- Producer Statement - Construction (PS3) from the applicator / installer
- Producer Statement - Construction Review (PS4) from an acceptable suitably qualified person
- Other information required by the BCA in the Building Consent Approval documents.

1238 AS-BUILT DOCUMENTATION

- Wiring diagrams
- Product datasheets
- As-built window drawings
- Installation instructions
- End-user manuals
- Maintenance requirements
- Service and maintenance schedule
- Provide draft as-built information prior to Practical Completion.
- Provide final as-built information prior to the end of the defects liability period. BT Installation

MP2 Installation

- **Clause G4 Ventilation:** Performance G4.3.1, G4.3.3(f), G4.3.3(g), G4.3.3(h)

MP2 is certified to NZS4211 having been tested to AS/NZS4420.1

- AS/NZS 1170.2 Structural design actions, part 2: wind actions.
- NZS 1170.5 Structural design actions - part 5: earthquake actions - New Zealand
- Air Infiltration Test / Positive 0.22 L/s m² & Negative 0.22 L/s m²
- Water Penetration Test / Up to 800 Pa
- Ultimate Strength Test / Up to 8000 Pa
- Deflection Test / Up to 3000 Pa
- Thermal Performance /U-Value (subject to glass makeup)

MP2 Testing

- **Clause H1 Energy efficiency :** Performance H1.3.1(a), H1.3.1(b), H1.3.3(a), H1.3.3(c), H1.3.3(d), H1.3.3(f), H1.3.4(a)

- NZBC E2/AS1 External moisture
- NZS 4211:1985 Performance of windows
- section 4521 ALUMINIUM WINDOWS AND DOORS

MP2 is certified to NZS4211 having been tested to AS/NZS4420.1.

- Air Infiltration Test / Positive 0.22 L/s m² & Negative 0.22 L/s m²
- Water Penetration Test / Up to 800 Pa
- Ultimate Strength Test / Up to 8000 Pa
- Deflection Test / Up to 3000 Pa
- Thermal Performance /U-Value (subject to glass makeup)

MP2 Thermal Performance Test

Notes

The MP2 is designed as an energy efficient glass louvre system, it creates sustainability within the building envelope and also provides life safety by means of smoke relief / smoke ventilation.

The louvre systems sustainability works in conjunction with selected sensors: CO2 sensors / Internal & external temperature sensors / rain sensor / wind, speed & directional sensor.

EBSA Automated Louvres MP2 Louvre System PTS

Product Technical Statement: 114183



The louvre systems smoke ventilation works in conjunction with the smoke detection system / sprinkler flow valve system

Evidence

The product meets the requirements set out in the following documents, or relevant parts of cited standards within the documents:

MP2 louvre system has been designed for the purpose of natural ventilation in buildings, it's design is to assist in architectural sustainability requirements which comprises of a framed or frameless aluminium assembly and blade holders which are thermally broken.

The system is manufactured and supplied in two options, double glazed 32mm stepped IGU or triple glazed 42mm stepped IGU which is assisting towards the H1 compliancy design.

MP2 louvre system has been designed for the purpose of smoke relief in buildings, it's design is to assist in the fire engineers requirements for life safety. The system is operated by means of automated 24v d/c extra low voltage field cabling.

Its usages are, but not limited to commercial / educational / industrial / residential sectors.

MP2 requirements are custom fabricated for each individual project. MP2 is a glazed operable unit with insulated glass IGU's and requires support structures upon installation, the support structures are / but not limited to timber support framing / steel support framing / aluminium support framing.

<https://ebsa.com.au/mp2-series/>

Supporting Evidence

The product has and can make available the following additional evidence to support the above statements:



Azuma Design Pty Ltd

[Wind and Water Penetration Testing - AZT0152.21](#)

Use in Service History

The MP2 is a large format thermally broken double or triple glazed louvre system designed for integration into commercial curtain wall systems.

The MP2 has established itself as the default solution for commercial projects and holds many performance records when tested to AS/NZS 4420.1. This includes its ability to withstand incredibly high wind loads (partly as a result of an integrated mechanical lock on every blade), resist the penetration of water (up to 800 Pascals) and pass air infiltration for air conditioned spaces

Product Criteria

Design requirements

MP2 louvre is designed for, but is not limited to, use in projects within the following scope:

Not limited to any building including housing and residential apartment buildings / commercial towers / industrial / educational

Not limited to Install into timber / steel and aluminium framed construction

Wind zones up to and including extra high.

Thermal performance.

Its a repeatable element and is not restricted to height, but is restricted to width at a tested

Configuration, maximum dimensions, and weights of individual panels also apply, and are dependent on the panel type.

Maximum IGU thicknesses are 32 mm and 42mm stepped IGU.

Anodised or powder coated finish selected from the Standard RAL or Dulux colour ranges.

Air permeability rating (determined in accordance with SNZ TS 4211) and achieves an air infiltration rating for air-conditioned buildings (determined in accordance with NZS 4211). Controlling air permeability and infiltration helps prevent heat losses from buildings.

Installation requirements

RE-INSTALLATION REQUIREMENTS *

Do not commence installation unless all preparatory work is of the required standard.

All opening sizes are within manufactures tolerances

Support structures are securely anchored

CONFIRM PREPARATION OF OPENING IN FACADE

Confirm that all louvres have been prepared and ready for the installation and including all consumables.

Do not proceed with the installation until required preparatory work has been completed.

EBSA Automated Louvres MP2 Louvre System PTS

Product Technical Statement: 114183



Fix to comply with the reviewed shop drawings and installation details including sealant, seals and fixing positions.

CABLE

Contractor to provide 24v cabling between selected control panels and louvre system. Volt drop calculations must be followed as per the manufactures specifications.

FINAL FIXING - LOUVRE

Make sure louvre is plumb and securely fixed to support structure with the correct fixings.

Structural silicon is applied to louvre as per installation details.

Maintenance requirements

MAINTENANCE CONTRACT PROPOSAL

Preventative service and maintenance is a requirement for all buildings where automated facades consisting of operable louvres, are utilised for natural ventilation and/or smoke relief purposes.

Provide a proposed maintenance SLS (Service Level Agreement)

List the service and maintenance requirements

Installer's approval certificate from the manufacturer / importer / distributor.

Manufacturer's / supplier's warranty

Installer's / applicator's warranty

Producer Statement - Construction (PS3) from the applicator / installer

Producer Statement - Construction Review (PS4) from an acceptable suitably qualified person

Warrantees

5 years for manufacture of louvre windows & control gear.

2 years for installation of louvres and control gear.

Company Product Information

Environmental

Materials

ALUMINIUM EXTRUSIONS: Alloy designation to comply with AS/NZS 1866. Branded and extruded for anodising or powder coating. Alloy designation: AlMgSi EN-AW6060-T66.

Complying with AS/NZS 1734 of suitable thickness. Rolled for powder coating or anodising. Alloy designation: AlMgSi EN-AW6060-T66.

Rating Passed

To NZS 4211, including: deflection, air infiltration, water penetration, ultimate strength, torsional strength of sashes.

Quality Assurance



ISO 9001 (Quality Management)

Videos

[Working Projects MP2 Performance Louvre](#)

Building Product Information Requirements

Manufacturer

Legal Trading Name:

Schneider + Nölke Lamellenfenster GmbH

Business Email:

info@snl.de

Company Website:

<https://www.snl.de/EN/index.html>

Contact Number/s:

+64 +496-38142000
+49638142000

Importer

Legal Trading Name:

EBSA NZ Limited

EBSA Automated Louvres MP2 Louvre System PTS

Product Technical Statement: 114183



Business Email:

sales@ebsa.co.nz

Company Website:

www.ebsa.co.nz

Contact Number/s:

+64 09-8840025

Product Identifier

MP2 FRAMED OR FRAMELESS

Warnings

This product has no warnings associated with it.



Date last validated: **14 January 2025**



Date last updated: **14 January 2025**

Disclaimer: The Product Technical Statement (PTS) template is copyright to Construction Information Limited. However the content of this PTS is the responsibility of the product manufacturer/supplier. Refer to the miproducts Terms and Conditions