



PRODUCT ALUMAT 15 I

DESCRIPTION Extra Heavy Duty aluminium and infill entrance mat. This is our top-of-the-line line mat featuring extra

heavy profile and elevated infills for use inside or sheltered exterior situations..

USES Mat depth 15mm – 20mm with variable depth rubber base. Install in set downs 15mm to 20mm deep

FEATURES Elevated infills and robust extra thick exterior grade alloy ensure this product will perform for many years.

A 20 year warranty on the frames means infills can be economically replaced to keep the entrance looking fresh and new. Ezi-clean with no under mat soiling. For use both inside and sheltered exterior locations. Variable depth FULL rubber base instead of strips, and extra thick aluminium provides uniform cushioning

and weight distribution with no 'clatter' or distortion.

Fully interlocking allows for complex mat shapes which can be seamlessly joined to make any width or

depth mats.

Choose from our range of colour infills.

LIMITATIONS For use in set downs or matwells. For situations requiring additional surface water handling, see ALUMAT

15D.

Substrates must be properly prepared and level as per our specifications available on our website.

PERFORMANCE Complies with all Australian and New Zealand building code requirements, including the following

Fire safety. EN ISO 9239-1 Critical Flux ≥8 kw/m2.

Slip test compliant in both wet and dry situations. AS/NZS3661.1

MATERIALS Infills 100% air-entangled polypropylene with FR backing (fire retardant) made by leading Dutch

manufacturer, Vebe Floor Coverings for distribution in New Zealand exclusively by Alumat Flooring

Solutions.

1720g/m2, pile height 10mm.

Base frames are made from exterior grade satin anodised 6063-T5 magnesium alloy

WATER ABSORPTION Alumat rib infill is impervious to water by design, offering a superior way of dealing with

incoming dirt and water. The rigid polypropylene ribs scrape footwear and collect water and dirt in the troughs, keeping them away from shoe contact. Water evaporates, and as the non-absorbent fibres are stain resistant, they are easier to clean and stay looking clean for longer. Increase water collection or drainage is possible incorporating drain channels used with

Alumat 15D mats.

GUARANTEE ALUMAT 15I has a 20 year warranty on frames suitability for refitting with infills subject to correct

installation and maintenance.

PRICE INDICATION As at June 2017, ALUMAT 15 I is priced at \$619 per sq.m plus GST. (NZ freight free)

Alumat Flooring Solutions Data sheet Alumat 15 I. 1/9/17